

Zygology Limited

Call Free on 0808 123 1221 Email sales@zygology.com

Issue #1-2020

Fax 08458 12 12 21

www.zygology.com

Unit 7 Thame 40 Jane Morbey Road

> Thame OX9 3RR

ProGrip Rivet Nuts 2154- Steel Full Hex Low Profile Closed End Range

The most cost effective method of installing a full depth thread in thin gauge materials, ProGrip Rivet Nuts come in a variety of forms. Ideal for use in drilled or punched holes, ProGrip Rivet Nuts are installed from one side making them especially suitable for tube, box sections or tight corners. A comprehensive range of inserts is available in a large range of metric thread sizes to suit most applications.

The standard low profile head gives a near flush finish in sheet materials without the need to countersink the holes. To increase torque to turn values, splined inserts can be used as well as hex profile inserts in conjunction with matching pre-punched holes. Closed end inserts can be used to ensure that incorrect bolts cannot damage internal components, and improve resistance to ingress from fluids.

2154 Series Steel Full Hex Low Profile Closed End Range								
Thread Size	Part Number	Grip Range	Hole Size A/F -0.0 +0.1	D -0.1 + 0.07	L	Н	Ρ	
M4 X 0.7	2154-0425	0.5-2.5	6.0	5.9	16.0	7.0	0.5	All dimensions in millimetres Steel inserts are supplied
M5 X 0.8	2154-0530	0.5-3.0	7.0	6.9	20.0	8.0	0.5	Zinc Plated All plating materials are
M6 X 1.0	2154-0635	0.5-3.5	9.0	8.9	20.5	10.00	0.6	RoHS / WEEE compliant
M8 X 1.25	2154-0840	1.0-4.0	11.0	10.9	23.00	12.0	0.65	

Zygology Rivet Nut Tools

Zygology offers a comprehensive range of air, battery and hand operated tools a vailable to choose from on the placing tools page of our website. These can be found by <u>clicking here</u> or by going to:

www.zygology.com/productcart/pc/Tools-for-rivet-nuts.html

If you need assistance deciding which is the right tool for you please call us free on 0808 123 1221 and we will be happy to advise you of the best tool for your requirements

