

6.4 mm Stainless Steel Blind Rivet with a wide Grip Range

The Avinox® XT is a high strength, stainless steel breakstem fastener with excellent bulbing tail formation, which makes it ideal for the use in thin sheet materials. The new Avinox® XT fastener features a wide grip range, especially suited for applications with varying sheet thicknesses. It is designed for use in applications such as automotive, truck and trailer, heating and ventilation, domestic appliances, industrial equipment and renewable energies.



Features and Benefits

- Excellent corrosion performance
- Temperature fluctuation resistance
- High shear and tensile strength
- High residual clamp load
- Multi-grip capability
- Resists vibration and joint slippage
- Good blind side footprint and bulb formation
- Spreads the tail bearing load/clamp load on the rear sheet
- Reliable stem retention
- Suitable also in softer materials (see test report)
- Under head recess accommodates burrs around holes and spreads the load evenly on the top sheet

Installation Tools

The Avinox® XT fastener is installed securely in seconds with the Genesis® nG4 model.

Complete tool	part no. 71233-00083
Nose assembly	part no. 71233-15000
Nose tip	part no. 71233-15002

Specifications

Part Number Grip range	0BE61-00815 1.5 - 5.5 mm
Part Number Grip range	0BE61-00819 5.0 - 9.0 mm
Material	Stainless Steel
Surface finish - body - stem	bright finish natural
Body diameter	6.4 mm
Hole diameter	6.6 - 7.0 mm
Shear strength*	14.3 kN (through stem)
Tensile strength*	8.0 kN
Stem push-out typical	3.0 kN

^{*} Performance values are typical with test method according to ISO 14589 (2000).

Assembly Applications

Industrial refrigeration Solar panels









For more information please contact your local STANLEY Engineered Fastening representative.

STANLEY Engineered Fastening

www.StanleyEngineeredFastening.com

© 2014 Stanley Black & Decker, Inc., Rev. 10.2014

Your local contact is: Zygology Ltd • Unit 7, Thame 40 Jane Morbey Road • Thame, OX9 3RR Tel: 0808 123 1221 • sales@zygology.com

